

cAP ac


The cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz and 5 GHz in 802.11ac and legacy standards, and will provide coverage in 360 degrees around it.

Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE input on the first port, and passive PoE output on the second port.



The cAP ac is a feature packed device with a sleek enclosure, that can become inconspicuous with the push of a button - the customizable mode button in the device center will turn off all lights and sounds at it's default configuration, but can be reconfigured to launch any RouterOS script.

The device comes bundled with two enclosures, so you can choose the design you like best.



24 V 1.2 A
power adapter



Ceiling mount



Gigabit PoE injector



K-46 screw kit

Specifications


Product code	RBcAPGi-5acD2nD (International) RBcAPGi-5acD2nD-US (USA)			
CPU	4 cores, IPQ-4018			
CPU nominal frequency	716 MHz			
Memory	128 MB			
Storage type	Flash			
Storage size	16 MB			
10/100/1000 Ethernet ports	2			
Wireless	2.4 GHz	5 GHz		
Wireless regulations	Specific frequency range may be limited by country regulations			
Operating frequency	International	2412 - 2484 MHz	International	5150 - 5875 MHz
	USA	2412 - 2462 MHz	USA	5170 - 5250 MHz 5725 - 5835 MHz
Protocols	802.11b/g/n		802.11ac	
Number of chains	2		2	
Antenna gain	2 dBi		2.5 dBi	
Wireless regulations	Specific frequency range may be limited by country regulations			
Power options	PoE-in 802.3af/at, PoE-out (Passive, Ethernet port 2), 17-57 V			
Consumption	13 W			
Dimensions	Round case: ø 136 mm, height: 30 mm; Square case: 145 mm x 145 mm x 30 mm			
Operating temperature	-40°C .. +70°C tested			
LEDs	7x LEDs (1x user LED)			
License level	4			
Operating system	RouterOS			

Wireless specifications

Rate (2.4 GHz)	Tx	Rx
1MBit/s	26	-100
11MBit/s	26	-94
6MBit/s	26	-96
54MBit/s	23	-78
MCS0	26	-96
MCS7	22	-73

Rate (5 GHz)	Tx	Rx
6MBit/s	26	-96
54MBit/s	21	-80
MCS0	26	-96
MCS7	20	-75
MCS9	18	-70

Network example



The cAP ac is equipped with two Ethernet ports, allowing you to connect another device, to further extend your network. What's more, the second Ethernet port supports 802.3af/at PoE output, so it can power a wide variety of RouterBOARDS and other devices, like IP cameras. In the following scenario, you can use a central hEX PoE device to power all your cAP ac units, and then have cAP lite units connected to provide even better coverage. The hEX PoE can even be used as a CAPsMAN server, so you can easily manage all your access points, and control all their settings in a single device.