

Let Your Business Go Mobile with Ease



AURA PP-6906W

3" Web Printer

The AURA PP-6906W features a web server technology that enables web based printing from virtually any Android, iOS or Windows based devices.

AURA PP-6906W



Features:

- Android, iOS and Windows support
- Embedded Linux + HTTP server
- LAN and WiFi 2-in-1 interface
- Allows OS independent printing from SOAP/HTTP-supported devices
- No separate web server is required for printing

Specification

AURA PP-6906W

Print Speed	Up to 200 mm/sec	
Paper Width	80mm	58mm
Print Resolution	180 dpi x 180 dpi (W x H)	
Printing Width	512 dots	424 dots
Font	Font A, Font B	
Default Line Feed Space	30 dots	
Color Specification	Black only	
Raster Image <image>	Monochrome image	
Logo <logo>	Monochrome image	
Bar Code <barcode>	UPC-A, UPC-E, EAN13, JAN13, EAN8, JAN8, CODE39, ITF, CODABAR, CODE93, CODE128	
Two-Dimensional Code <symbol>	PDF417, QR Code	
Page Mode Default Area	512 dots x 831 dots (W x H)	360 dots x 831 dots (W x H)
Page Mode Maximum Area	512 dots x 1662 dots (W x H)	360 dots x 1662 dots (W x H)
Paper Cut <cut>	Cut, Feed cut	
Drawer Kick-Out <pulse>	Supported	
Forced transmission mode	Supported	
Recovery from an error <recovery>	Supported	
Reset <reset>	Supported	
Command <command>	Supported	

Characters in a Line

Font A	12" TFT LCD	
Font B	1024 x 768	

Character Size

Font A	ANK: 12 dots x 24 dots (W x H)	ANK: 35 characters
Font B	ANK: 8 dots x 16 dots (W x H)	ANK: 47 characters

Character Baseline

Font A	At the 21st dot from the top of the character
Font B	At the 15th dot from the top of the character

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

* The product information and specifications are subject to change without prior notice.

Certifications		EN201710V2
----------------	--	------------



POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
 Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
 Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller